

Globe Post Lights



Pole Light Park Globe Reflex

Decorative and blindfree post top lantern in differnt heights. Energy economizing.

Globe in acrylic UV stabilized with 400 mm diameter. The globe is available in transparent or top black mirrored. (At higher quantities optionally polycarbonate or 250 or 300mm or opal or smoked finish available.)
E27 porcelain lamp holder. With included ballast.
Available for 80w mercury lamp (as bright as 220W incandescent lamp) or 70w sodium lamp (as bright as 340 watt incandescent lamp) or compact fluoresent lamp 42W GX24q-4.
For pole mount 60mm diameter. (Please order lamp and pole extra)
Protection class IP44, insulation class II
LT-2000



Pole Light Globe Norm

Decorative and blindfree post top lantern in differnt heights.

Globe in acrylic UV stabilized with 400 mm diameter. The globe is available in transparent or top black mirrored. (At higher quantities optionally polycarbonate or 250 or 300mm or opal or smoked finish available.)
E27 porcelain lamp holder.
For incandescent lamps up to 100W and for self-ballasted compact fluoresent lamps.
For pole mount 60mm diameter. (Please order lamp and pole extra)
Protection class IP44, insulation class II
Please see also our LT-2000 Park Reflex for higher light outputs with discharge lamps or the LED model.
LT-2001



Pole Light LED Globe

Decorative post top lantern in differnt heights.
LT-2001L



Globe in acrylic UV stabilized with 400 mm diameter. The globe is available in transparent or top black mirrored. (At higher quantities optionally polycarbonate or 250 or 300mm or opal or smoked finish available.)
Including SMD LED lamp 13W. The brightness is alike 100 watt halogen light.
For pole mount 60mm diameter. Please order the pole extra.
Protection class IP44, insulation class II
Please see also our LT-2000 Park Reflex for higher light outputs with discharge lamps.
Weight: 2,2 kg

Straight Steel Poles



Glass Fiber Pole for Garden Light 3m
LT-2003



Lantern Light Post Aluminium Lightweight 3m
LT-2004

Street Lamps Lantern



Park Street Light Lantern Avenue 70W

Decorative and blindfree post top lantern fixture for HPS sodium lamp.

Die-cast aluminium base in RAL 9006 grey colour (alternatively black or white).
 UV stabilized acrylic transparent screen (on request polycarbonate).
 Corrosion, seawater and salty humidity resistant.
 Internal louvre compliant with most restrictive standards in terms of light pollution.
 Ample aluminium reflecting cap, painted outside in base colour and white inside.
 With silicon rubber sealing.
 The electrical connection is made via a connector plug for better service-friendliness. The matching connector is included.
 E27 porcelain lamp holder
 For mounting on poles with 60 mm diameter.
 Requires a high pressure sodium lamp or metal halide discharge lamp 70 watt.
 The lamp has to be ordered extra.
 Alternatively available as LED version.
 Protection degree: IP66
 Insulation class II
 Dimensions: diameter 450mm, height 418mm.
 LT-2010



LED Park Street Light Lantern Avenue 15W (150W)



Decorative and blind-free post top LED lantern fixture with energy economizing LED.
 LT-2011

Die-cast aluminium base in RAL 9006 grey colour (alternatively black or white).
 UV stabilized acrylic transparent screen (on request polycarbonate).
 Corrosion, seawater and salty humidity resistant.
 Internal louvre compliant with most restrictive standards in terms of light pollution.
 Ample aluminium reflecting cap, painted outside in base colour and white inside.
 With silicon rubber sealing.
 The electrical connection is made via a connector plug for better service-friendliness. The matching connector is included.
 Including power SMD LED lamp 15W.
 The LED can be replaced directly on the mast within less than a minute.
 Luminous flux: 1500 Lm
 Light color 4000K pure white (at 10 pcs also 3000K warm white)
 Light emission: 360 degrees circular
 Especially economical - high efficiency of the lamp -
 The brightness is comparable with 50W HQL mercury vapor lamp or a 50W sodium vapor lamp.
 Life span: > 50,000 hrs
 Mushroom LED lights do not emit UV light and thereby attract no insects.
 The light stays longer clean and thus without cobwebs.
 The LED mushroom light is virtually maintenance free, has a very long service life, only need a quarter of the electricity as conventional mercury vapor lamps.
 The light is comfortable warm, lit evenly and not hidden in the surrounding windows.
 Including LED supply unit.
 Operating voltage 230V (85 ... 265V AC) 50 / 60Hz
 Power consumption: 15 watts
 Integrated power stabilization, which ensures even with fluctuating line voltage for constant light intensity.
 For mounting on poles with 60 mm diameter.
 Ambient temperature: -40°C ... +45°C
 Protection degree: IP66
 Insulation class II
 Dimensions: diameter 450mm, height 418mm.
 Weight: 4,3 kg



LED Park Street Light Lantern Avenue 20W (200W)

Decorative and blind-free post top LED lantern fixture with energy economizing LED.
 LT-2013

LED Street Lighting



LED Street Light Bell Shape

Decorative Luminaire with bracket arm for public garden, city center, bridge and market place, etc.

Economical and decorative LED street light pole and luminaire.
Lamp made of cast aluminum, powder-coated or painted in RAL color of your choice
Frosted or clear PMMA cover with bayonet mount, 400mm diameter
Average life expectancy of LEDs: 60,000 hours.
Optimal thermal management with liquid cooling of the LEDs without mechanical cooling fan, thus maintenance-free.
Very economical - high efficiency of the lamp.
Dimmable power LED lamp 32W.
Light color: Neutral white 3500K or warm white 2700K
Dimming possible of the entire light, to provide only the required brightness depending on the installation site.
Adjustable power reduction (half-night circuit) with a slow dimming transition, over second phase or 10V input.
5 LED segments are arranged cone-shaped to provide an uniform and large illuminating range.
Individual LED segments can be switched off, to have light emission only in selected directions,
Thus, each lamp can be adapted to the particular installation site quickly and efficiently on site.
This streetlight emits no UV light and thereby attracts no insects. The fixture stays clean longer and thus without cobwebs.
The Bell LED lights are almost maintenance-free, have very long lifetimes and require only a quarter of the current as conventional mercury vapor lamps.
The light is warm, evenly lit and not shining into the surrounding windows.
Including LED supply unit.
recommended mounting heights 4m to 7m
Ambient temperature -30 °C to +55 °C
Supply voltage: 220V - 240 V AC
LED current selectable between 35mA to 500mA
Protection class I, IP65
Overall dimensions: diameter 690mm, height 635mm.
Conversion of old lights on request!
LT-2014



LED Street Light Bell Shape

Decorative Luminaire with bracket arm for public garden, city center, bridge and market place, etc.

Economical and decorative LED street light pole and luminaire.
Lamp made of cast aluminum, powder-coated or painted in RAL color of your choice
Frosted or clear PMMA cover with bayonet mount, 400mm diameter
Average life expectancy of LEDs: 60,000 hours.
Optimal thermal management with liquid cooling of the LEDs without mechanical cooling fan, thus maintenance-free.
Very economical - high efficiency of the lamp.
Dimmable power LED lamp 32W.
Light color: Neutral white 3500K or warm white 2700K
Dimming possible of the entire light, to provide only the required brightness depending on the installation site.
Adjustable power reduction (half-night circuit) with a slow dimming transition, over second phase or 10V input.
5 LED segments are arranged cone-shaped to provide an uniform and large illuminating range.
Individual LED segments can be switched off, to have light emission only in selected directions,
Thus, each lamp can be adapted to the particular installation site quickly and efficiently on site.
This streetlight emits no UV light and thereby attracts no insects. The fixture stays clean longer and thus without cobwebs.
The Bell LED lights are almost maintenance-free, have very long lifetimes and require only a quarter of the current as conventional mercury vapor lamps.
The light is warm, evenly lit and not shining into the surrounding windows.
Including LED supply unit.
recommended mounting heights 4m to 7m
Ambient temperature -30 °C to +55 °C
Supply voltage: 220V - 240 V AC
LED current selectable between 35mA to 500mA
Protection class I, IP65
Overall dimensions: diameter 690mm, height 635mm.
Conversion of old lights on request!
LT-2014D



LED Street Light Bell

Decorative Luminaire with bracket arm for public garden, city center, bridge and market place, etc.

Economical and decorative LED street light & Column light.
 Cast aluminum luminaire coated or varnished in RAL-tone of your choice
 Cover PMMA beaded or clear with bayonet closure, diameter 400mm
 Mean life expectancy of the LEDs: 50,000 hours.
 Particularly economical - high efficiency of the lamp
 With LED bulb 33W
 The light intensity corresponds to approximately 70W NAV or 125W HQL or 350W halogen.
 Light color neutral white 3500K or warm white 2700K
 The LED bell light does not emit UV light and thus attracts little insects. The luminaire stays longer clean and without spider webs.
 The LED taillights are almost maintenance-free, have very long service lives, require only a quarter of the current, such as conventional mercury vapor lamps.
 The light is pleasantly warm, illuminates evenly and does not blend into the surrounding windows.
 Including LED supply unit.
 Recommended mast height: 4m to 7m
 Ambient temperature -30 ° C to + 55 ° C
 Connection voltage 230 V AC
 Protection class I, IP65
 Overall dimensions: diameter 560mm, height 619mm.
 LT-2020

Street Lamps Lantern



LED Urban Park Light Lantern Ring 60W



LT-2101

Decorative and blind-free post top LED lantern fixture with energy economizing LED.
 LT-2101

Die-cast aluminium base in RAL 9006 grey colour (alternatively black or white).
 UV stabilized acrylic transparent screen (on request polycarbonate).
 Corrosion, seawater and salty humidity resistant.
 Internal louvre compliant with most restrictive standards in terms of light pollution.
 Ample aluminium reflecting cap, painted outside in base colour and white inside.
 With silicon rubber sealing.
 The electrical connection is made via a connector plug for better service-friendliness. The matching connector is included.
 Including power SMD LED lamp 20W.
 The LED light source can be replaced directly on the mast within less than a minute.
 Luminous flux: 2005 Lm
 Light color 4000K pure white (at 10 pcs also 3000K warm white)
 Light emission: 360 degrees circular
 Especially economical - high efficiency of the lamp -
 The brightness is comparable with 70W HQL mercury vapor lamp or a 70W sodium vapor lamp.
 Life span: > 50,000 hrs
 Mushroom LED lights do not emit UV light and thereby attract no insects.
 The light stays longer clean and thus without cobwebs.
 The LED mushroom light is virtually maintenance free, has a very long service life, only need a quarter of the electricity as conventional mercury vapor lamps.
 The light is comfortable warm, lit evenly and not hidden in the surrounding windows.
 Including LED supply unit.
 Operating voltage 230V (85 ... 265V AC) 50 / 60Hz
 Power consumption: 20 watts
 Integrated power stabilization, which ensures constant light intensity, even with fluctuating line voltage.
 For mounting on poles with 60 mm diameter.
 Ambient temperature: -40°C ... +45°C
 Protection degree: IP66
 Insulation class II
 Dimensions: diameter 450mm, height 418mm.
 Weight: 8 kg

Classic Lighting Posts for Gardens and Pedestrian Precinct



GEO-Technik Germany



Triple Light Lamp Post Design 9132

Aluminium die-cast lantern candelabra with 3 lights, height 250cm, white.

Material: Aluminium die-cast, white.
(Other colours on request)
Height: 250cm
Protection: IP44
To use with lamp: 3x 100 watt, E27 (not included), we suggest energy saving lamp 23 watt.
LT-9133

Decorative Pole Lights for pedestrian precincts



LED Street Pole Light Unique Lantern



GEO-Technik Germany

Nice LED streetlight, also for public garden or pathways. Made in Germany. LT-9300

Very rigid and worthy construction.
Timeless design that fits into the old town, as well as in modern pedestrian zones, parks and footpaths.
Use: Riding lane lighting, footpath, park, driveway, pedestrian precinct, bicycle path, etc.
Without any pollution, Unique lights are energy saving and environmental protective, and they are very suitable to illuminate streets, schools, parks, villas, courtyards, gardens, and so on.
Hand welded, corrosion-protected with two-component primer and scratch resistant, provide multi-component paint truck.
With durable acrylic glass.
The light distribution is 360 degree round, to all directions.
Enlighted area aprx. 25m - 30m Ø
The aluminium lamelle reflector feeds the light slightly downwards and protects against blinding.
With high efficient power LED 15W or 20W
Light output 800 / 1200 Lumen - as bright as 50W / 80W HQL HPL mercury
Light colour 3500K warm white
Functions well under low temperature - 25° ... + 60° C.
Maintenance-free - Lifetime of the lamp aprx. 10 years.
Easily exchange of the LED light.
Operating voltage 200V - 240V 50 / 60Hz
Protection IP44, class II
Dimensions: Tiefe 300mm, Breite 450mm, Höhe 400mm
For poles with 60mm top diameter.
The steel pole 3, 4 or 5 meter height has to be ordered extra.
12 years spareparts availability.
Minimum ordering quantity 4 pcs. Preparing time aprx. 6 weeks
Weight: 5 kg



**LED Street Pole Light Old Style
Lantern 3m**



Nice and bright 30W LED streetlight, also for public garden or pathways.
Made in Europe.
LT-9302

Very rigid and worthy construction.
Timeless design that fits into the old town, as well as in modern pedestrian zones, parks and footpaths.
Use: Riding lane lighting, footpath, park, driveway, pedestrian precinct, bicycle path, etc.
Without any pollution, energy saving and environmental protective, and they are very suitable to illuminate streets, schools, parks, villas, courtyards, gardens, and so on.
Corrosion-protected with two-component primer and scratch resistant, provide multi-component paint truck.
The light distribution is 360 degree round, to all directions.
Lighted area aprx. 25m - 30m Ø
The LED optics feeds the light slightly downwards and protects against blinding.
With high efficient power LED 30W
Light output: 3000 Lumen - as bright as 70W sodium / 80W HQL HPL mercury
Light colour 4000K nature white
Wide ambient temperature range: - 20°C ... + 40°C
Maintenance-free - Lifetime of the lamp aprx. 10 years.
Operating voltage 200V - 240V 50 / 60Hz
Power factor: > 0,95
Protection IP65, class II
Shock proof: IK08
Wind load surface: 0,37m²
Dimensions: Width 420mm, depth 420mm, height 800mm
For poles with 60mm top diameter.
The steel pole 4, 5 or 6 meters height has to be ordered extra.
Minimum ordering quantity 2 pcs. Preparing time aprx. 3 weeks
Weight: 7,5 kg












**LED Street Pole Light Old Style
Lantern 40W**



Nice and bright 40W LED streetlight, also for public garden or pathways.
Made in Europe.
LT-9304

Very rigid and worthy construction.
Timeless design that fits into the old town, as well as in modern pedestrian zones, parks and footpaths.
Use: Riding lane lighting, footpath, park, driveway, pedestrian precinct, bicycle path, etc.
Without any pollution, energy saving and environmental protective, and they are very suitable to illuminate streets, schools, parks, villas, courtyards, gardens, and so on.
Corrosion-protected with two-component primer and scratch resistant, provide multi-component paint truck.
The light distribution is 360 degree round, to all directions.
Lighted area aprx. 25m - 30m Ø
The LED optics feeds the light slightly downwards and protects against blinding.
With high efficient power LED 40W
Light output: 4800 Lumen - as bright as 70W sodium / 80W HQL HPL mercury
Light colour 4000K nature white
Wide ambient temperature range: - 20°C ... + 40°C
Maintenance-free - Lifetime of the lamp aprx. 10 years.
Operating voltage 200V - 240V 50 / 60Hz
Power factor: > 0,95
Protection IP65, class II
Shock proof: IK08
Wind load surface: 0,37m²
Dimensions: Width 420mm, depth 420mm, height 800mm
For poles with 60mm top diameter.
The steel pole 4, 5 or 6 meters height has to be ordered extra.
Weight: 7,5 kg

	<p>Pole Light Fixture Berlin</p> <p>Decorative classical lighting fixture for pedestrian precinct, market place, walking way, park, harbour, etc.</p>	<p>classically designed lighting fixture. height of pole: 3m. for edison lightbulb E27 100W or energy-saving lamp E27. please order the lamp separately. pole: 3m with inspection door. material: aluminium die-cast. Lamp bowls made of polycarbonate, ø 300mm. Available with one or two lampshades. Polyester powder paint coating which is highly resistant to corrosion and sea mist. available colours: antracite (alternatively silver-gray). protection class: IP43 incl. appropriate ground anchorage hardware. LT-9350</p>
	<p>Pole Light Fixture Munich</p> <p>Decorative modern lighting fixture for pedestrian precinct, market place, walking way, park, harbour, etc.</p>	<p>classically designed lighting fixture. height of pole: 3m. for edison lightbulb E27 100W or energy-saving lamp E27. please order the lamp separately. pole: 3m with inspection door. material: aluminium die-cast. Lamp bowls made of polycarbonate, ø 300mm. Available with one or two lampshades. Polyester powder paint coating which is highly resistant to corrosion and sea mist. available colours: antracite (alternatively silver-gray). protection class: IP43 incl. appropriate ground anchorage hardware. LT-9354</p>
	<p>LED Pole Light Fixture Munich</p> <p>Decorative modern lighting fixture for pedestrian precinct, market place, walking way, park, harbour, etc.</p>	<p>for edison lightbulb E27 100W or energy-saving lamp E27. please order the lamp separately. pole: 3m with inspection door. material: aluminium die-cast. Lamp bowls made of polycarbonate, ø 300mm. Polyester powder paint coating which is highly resistant to corrosion and sea mist. available colours: antracite (alternatively silver-gray). protection class: IP43 incl. appropriate ground anchorage hardware. LT-9355</p>
	<p>Street Pole Light Cabinet</p> <p>design lighting fixture for illumination and lighting of areas like footpaths, car parks and so on</p>	<p>innovatively designed lighting fixture. height: 4.50m. For lamp HQI - G12 70W or 150W available colours: white / silver-grey / anthracite incl. low-loss conventional ballast, 220 - 240V please order the lamp extra, recommend distance between two fixtures: 13m pole: 5.20m (70cm are embedded into the ground) material: aluminium die-cast and stainless steel diffusor made of 5mm tempered glass. thermal shock and impact resistant external diffusor made of diffusing white aluminium plate / prismatic aluminium polyester powder paint coating which is highly resistant to corrosion and sea mist available versions: with one lamp-head, for indirect illumination with two lamp-heads, for indirect illumination with two lamp-heads, for direct and indirect illumination protection class: IP54 LT-9370</p>
	<p>LED Pole Light Fixture Rouen 4m</p> <p>Classical lighting fixture designed for residential areas, parks, drives, arcades, pedestrian precinct, public garden.</p>	<p>Stable quality, made in EU Including LED lamp E27 / 20W Light colour: 4000K pure white (on order in 3000K warm white) Luminous flux: 2020 Lm - comparable to 200 watt halogen light. Voltage: 220 - 240V Frequency: 50 - 60Hz Pole: 4.00m Steel galvanized + decorative hard foam cover material: aluminium die-cast available colours: white / silver-grey / anthracite lampshade made of glass polyester powder paint coating which is highly resistant to corrosion and sea mist available versions: with one or two lamp-heads, Lamp head diameter: 560mm protection class: IP43 the fixture is supplied with appropriate ground anchorage hardware The concrete foundation is not included LT-94R41-2</p>

 <p>LT-94-41</p>		<p>LED Pole Light Fixture 4m Rouen 30W</p>	<p>Stable quality, made in EU Including LED board 30W and driver Light colour: 4000K pure white (on order in 3000K warm white) Luminous flux: 3030 Lm - comparable to 300 watt halogen light. Voltage: 220 - 240V Frequency: 50 - 60Hz Pole: 4.00m Steel galvanized + decorative hard foam cover material: aluminium die-cast available colours: white / silver-grey / anthracite lampshade made of glass polyester powder paint coating which is highly resistant to corrosion and sea mist available versions: with one or two lamp-heads, Lamp head diameter: 560mm protection class: IP43 the fixture is supplied with appropriate ground anchorage hardware The concrete foundation is not included LT-94R41-3</p>
 <p>LT-94-52</p>		<p>LED Pole Light Fixture Rouen Double Arm 5m</p>	<p>Stable quality, made in EU Including 2 x LED lamps E27 / 20W Light colour: 4000K pure white (on order in 3000K warm white) Luminous flux: 2020 Lm - comparable to 200 watt halogen light. Voltage: 220 - 240V Frequency: 50 - 60Hz Pole: 5.00m Steel galvanized + decorative hard foam cover Light fixture material: aluminium die-cast available colours: white / silver-grey / anthracite lampshade made of glass polyester powder paint coating which is highly resistant to corrosion and sea mist available versions: with two lamp-heads, with 3 lamp-heads protection class: IP43 the fixture is supplied with appropriate ground anchorage hardware The concrete foundation is not included LT-94R52</p>