



Decorative Pole Lights for pedestrian precincts

		<p>Pole Light Park Globe Reflex</p>	<p>Globe in acrylic UV stabilized with 400 mm diameter. The globe is available in transparent or top black mirrored. (At higher quantities optionally polycarbonate or 250 or 300mm or opal or smoked finish available.) E27 porcelain lamp holder. With included ballast. Available for 80w mercury lamp (as bright as 220W incandescent lamp) or 70w sodium lamp (as bright as 340 watt incandescent lamp) or compact fluorescent lamp 42W GX24q-4. For pole mount 60mm diameter. (Please order lamp and pole extra) Protection class IP44, insulation class II LT-2000</p>
		<p>Pole Light Globe Norm</p>	<p>Globe in acrylic UV stabilized with 400 mm diameter. The globe is available in transparent or top black mirrored. (At higher quantities optionally polycarbonate or 250 or 300mm or opal or smoked finish available.) E27 porcelain lamp holder. For incandescent lamps up to 100W and for self-ballasted compact fluorescent lamps. For pole mount 60mm diameter. (Please order lamp and pole extra) Protection class IP44, insulation class II Please see also our LT-2000 Park Reflex for higher light outputs with discharge lamps or the LED model. LT-2001</p>
	<p>Pole Light LED Globe</p>		<p>Decorative post top lantern in differnt heights. LT-2001L</p> <p>Globe in acrylic UV stabilized with 400 mm diameter. The globe is available in transparent or top black mirrored. (At higher quantities optionally polycarbonate or 250 or 300mm or opal or smoked finish available.) Including SMD LED lamp 13W. The brightness is alike 100 watt halogen light. For pole mount 60mm diameter. Please order the pole extra. Protection class IP44, insulation class II Please see also our LT-2000 Park Reflex for higher light outputs with discharge lamps. Weight: 2,2 kg</p>

Accessories for outdoor fixtures

-  Glass Fiber Pole for Garden Light 3m
LT-2003
-  Lantern Light Pole 4m
LT-2004

Street Lamps Lantern



Park Street Light Lantern Avenue 70W

Decorative and blindfree post top lantern fixture for HPS sodium lamp.

Die-cast aluminium base in RAL 9006 grey colour (alternatively black or white).
 UV stabilized transparent acrylic screen (on request polycarbonate prismatic).
 Corrosion, seawater and salty humidity resistant.
 Internal louvre compliant with most restrictive standards in terms of light pollution.
 Ample aluminium reflecting cap, painted outside in base colour and white inside.
 With silicon rubber sealing.
 The electrical connection is made via a connector plug for better service-friendliness. The matching connector is included.
 E27 porcelain lamp holder
 For mounting on poles with 60 mm diameter.
 Version for high pressure sodium lamp and metal halide discharge lamp 70 watt.
 or for other lamp types.
 Alternatively available as LED version.
 The lamp has to be ordered extra.
 Protection degree: IP66
 Insulation class II
 Dimensions: diameter 450mm, height 418mm.
 LT-2010



LED Park Street Light Lantern Avenue 15W (150W)

Decorative and blind-free post top LED lantern fixture with energy economizing LED.
 LT-2011



Die-cast aluminium base in RAL 9006 grey colour (alternatively black or white).
 UV stabilized transparent acrylic screen (on request polycarbonate prismatic).
 Corrosion, seawater and salty humidity resistant.
 Internal louvre compliant with most restrictive standards in terms of light pollution.
 Ample aluminium reflecting cap, painted outside in base colour and white inside.
 With silicon rubber sealing.
 The electrical connection is made via a connector plug for better service-friendliness. The matching connector is included.
 Including power SMD LED lamp 15W.
 The LED can be replaced directly on the mast within less than a minute.
 Luminous flux: 1500 Lm
 Light color 4000K pure white (at 10 pcs also 3000K warm white)
 Light emission: 360 degrees circular
 Especially economical - high efficiency of the lamp -
 The brightness is comparable with 50W HQL mercury vapor lamp or a 50W sodium vapor lamp.
 Life span: > 50,000 hrs
 Mushroom LED lights do not emit UV light and thereby attract no insects. The light stays longer clean and thus without cobwebs.
 The LED mushroom light is virtually maintenance free, has a very long service life, only need a quarter of the electricity as conventional mercury vapor lamps.
 The light is comfortable warm, lit evenly and not hidden in the surrounding windows.
 Including LED supply unit.
 Operating voltage 230V (85 ... 265V AC) 50 / 60Hz
 Power consumption: 15 watts
 Integrated power stabilization, which ensures even with fluctuating line voltage for constant light intensity.
 For mounting on poles with 60 mm diameter.
 Ambient temperature: -40°C ... +45°C
 Protection degree: IP66
 Insulation class II
 Dimensions: diameter 450mm, height 418mm.
 Weight: 4,3 kg



LED Park Street Light Lantern Avenue 20W (200W)

Decorative and blind-free post top LED lantern fixture with energy economizing LED.
 LT-2013

LED Street Lighting



LED Street Light Bell Shape

Decorative Luminaire with bracket arm for public garden, city center, bridge and market place, etc.

Economical and decorative LED street light pole and luminaire.
 Lamp made of cast aluminum, powder-coated or painted in RAL color of your choice
 Frosted or clear PMMA cover with bayonet mount, 400mm diameter
 Average life expectancy of LEDs: 60,000 hours.
 Optimal thermal management with liquid cooling of the LEDs without mechanical cooling fan, thus maintenance-free.
 Very economical - high efficiency of the lamp.
 Dimmable power LED lamp 32W.
 Light color: Neutral white 3500K or warm white 2700K
 Dimming possible of the entire light, to provide only the required brightness depending on the installation site.
 Adjustable power reduction (half-night circuit) with a slow dimming transition, over second phase or 10V input.
 5 LED segments are arranged cone-shaped to provide an uniform and large illuminating range.
 Individual LED segments can be switched off, to have light emission only in selected directions,
 Thus, each lamp can be adapted to the particular installation site quickly and efficiently on site.
 This streetlight emits no UV light and thereby attracts no insects. The fixture stays clean longer and thus without cobwebs.
 The Bell LED lights are almost maintenance-free, have very long lifetimes and require only a quarter of the current as conventional mercury vapor lamps.
 The light is warm, evenly lit and not shining into the surrounding windows.
 Including LED supply unit.
 recommended mounting heights 4m to 7m
 Ambient temperature -30 °C to +55 °C
 Supply voltage: 220V - 240 V AC
 LED current selectable between 35mA to 500mA
 Protection class I, IP65
 Overall dimensions: diameter 690mm, height 635mm.
 Conversion of old lights on request!
 LT-2014



LED Street Light Sigma

Decorative Luminaire with bracket arm for public garden, city center, bridge and market place, etc.

Economical and decorative LED street light pole and luminaire.
 Lamp made of cast aluminum, powder-coated or painted in RAL color of your choice
 Frosted or clear PMMA cover with bayonet mount, 400mm diameter
 Average life expectancy of LEDs: 50,000 hours.
 Very economical - high efficiency of the lamp.
 Dimmable power LED lamp 36W.
 Light color: Neutral white 3500K or warm white 2700K
 This streetlight emits no UV light and thereby attracts no insects. The fixture stays clean longer and thus without cobwebs.
 The Bell LED lights are almost maintenance-free, have very long lifetimes and require only a quarter of the current as conventional mercury vapor lamps.
 The light is warm, evenly lit and not shining into the surrounding windows.
 Including LED supply unit.
 recommended mounting heights 4m to 7m
 Ambient temperature -30 °C to +55 °C
 Supply voltage: 220V - 240 V AC
 Protection class I, IP65
 Overall dimensions: diameter 690mm, height 635mm.
 Conversion of old lights on request!
 LT-2016

Lighting Posts for Gardens and Parks



Double Light Lamp Post Classic Design

Aluminium die-cast lantern candelabra with 2 lights, for public gardens. Height 230cm.

Material: Aluminium die-cast, black.
 (Other colours on request)
 Height 230cm
 Protection: IP44
 To use with lamp: 2x 100 watt, E27 (not included), we suggest energy saving lamp 23 watt.
 LT-9132



Triple Light Lamp Post Design 9132

Aluminium die-cast lantern candelabra with 3 lights, height 250cm, white. LT-9133



Triple Lamp Post Light Park Design Globe

Aluminium die-cast lantern candelabra with 3 globe lights, height 250cm, black. LT-9210

Decorative Pole Lights for pedestrian precincts



LED Street Pole Light Unique Lantern

Nice LED streetlight, also for public garden or pathways. Made in Germany. LT-9300







Very rigid and worthy construction. Timeless design that fits into the old town, as well as in modern pedestrian zones, parks and footpaths. Use: Riding lane lighting, footpath, park, driveway, pedestrian precinct, bicycle path, etc. Without any pollution, Unique solar lights are safe, energy saving and environmental protective, and they are very suitable to illuminate streets, schools, parks, villas, courtyards, gardens, and so on. Hand welded, corrosion-protected with two-component primer and scratch resistant, provide multi-component paint truck. With durable acrylic glass. The light distribution is 360 degree round, to all directions. Enlighted area aprx. 25m - 30m Ø. The aluminium lamelle reflector feeds the light slightly downwards and protects against blinding. With high efficient power LED 15W or 20W. Light output 800 / 1200 Lumen - as bright as 50W / 80W HQL HPL mercury. Light colour 3500K warm white. Functions well under low temperature - 25° ... + 60° C. Maintenance-free - Lifetime of the lamp aprx. 10 years. Easily exchange of the LED light. Operating voltage 200V - 240V 50 / 60Hz. Protection IP44, class II. Dimensions: Tiefe 300mm, Breite 450mm, Höhe 400mm. For poles with 60mm top diameter. The steel pole 3, 4 or 5 meter height has to be ordered extra. 12 Jahre Verfügbarkeitsgarantie für Ersatzteile. Minimum ordering quantity 4 pcs. Preparing time aprx. 6 weeks. Weight: 5 kg



Street Pole Light Cabinet

design lighting fixture for illumination and lighting of areas like footpaths, car parks and so on

innovatively designed lighting fixture. height: 4.50m. For lamp HQI - G12 70W or 150W available colours: white / silver-grey / anthracite incl. low-loss conventional ballast, 220 - 240V please order the lamp extra, recommend distance between two fixtures: 13m pole: 5.20m (70cm are embedded into the ground) material: aluminium die-cast and stainless steel diffuser made of 5mm tempered glass. thermal shock and impact resistant external diffuser made of diffusing white aluminium plate / prismatic aluminium polyester powder paint coating which is highly resistant to corrosion and sea mist available versions: with one lamp-head, for indirect illumination with two lamp-heads, for indirect illumination with two lamp-heads, for direct and indirect illumination protection class: IP54 LT-9370

 <p>LT-94-41</p>		<p>Pole Light Fixture Rouen 4m</p>	<p>classically designed lighting fixture. Including LED lamp E27 / 20W available colours: white / silver-grey / anthracite Light colour: 4000K pure white Voltage: 220 - 240V pole: 4.00m Steel + hard foam cover material: aluminium die-cast lampshade made of glass polyester powder paint coating which is highly resistant to corrosion and sea mist available versions: with one or two lamp-heads, protection class: IP43 the fixture is supplied with appropriate ground anchorage hardware LT-94-41</p>
 <p>LT-94-52</p>		<p>Pole Light Fixture Rouen Double Arm 5m</p>	<p>classically designed lighting fixture. Including 2 x LED lamps E27 / 20W available colours: white / silver-grey / anthracite Light colour: 4000K pure white Voltage: 220 - 240V pole: 5.00m Steel + hard foam cover material: aluminium die-cast lampshade made of glass polyester powder paint coating which is highly resistant to corrosion and sea mist available versions: with two lamp-heads, with 3 lamp-heads protection class: IP43 the fixture is supplied with appropriate ground anchorage hardware LT-94-52</p>